

COLUMN DRILL MACHINE FOLLOW B50E

Ref: B50E FOLLOW



Tech specs

Brand	FOLLOW
Drilling capacity in steel 60kg	50
Drilling capacity cast iron 200HB	60
Capacity steel thread 60Kg	M-36
Tapping capacity in cast-iron 200 HB	M-42
Transmission	Engranes
Automatic feed	Si
Clutch	Electromagnético
Feed number and range	4 (0,1 - 0,2 - 0,3 - 0,4)
Speed number and range	(12) 52-1400
Power of the main motor	3
Tapper	MT4
Spindle travel	240
Distance spindle center/ column	360
Column diameter	180
Table surface	580x460
Base surface	445x435
Max. distance between the spindle and the table	585
Distance max. between spindle to base	1170
Base T slot size	2-T14
Electrical voltage	220-380 V - 50/60 Hz
Dimensions (length x width x height)	950x680x2405
Net/ brut weigth	670/730



Standard equipment

- Digital display R.P.M.
- Depth readout display
- Powered table
- Tilting and swivel table
- Depth setting
- Drill ejector
- Coolant system
- Tapping system with turning inversion
- 3 MT sleeve
- Drill chuck capacity 1-13mm
- Sensitive Wheel
- Work Light
- Tool box
- CE certificate

Images

