

AUTOMATIC SURFACE GRINDER FOLLOW RSA800

Ref: RSA800 FOLLOW



Tech specs

Brand	FOLLOW
Surface worktable	800x400
Max. rectification area	800x400
Max. work table longitudinal travel	920
Max. cross travel of the table	450
Max. distance between the spindle center/ table	580
Max. load of magnetic chuck	700
Velocidad husillo (rpm)	1450
Table speed	5-25
Automatic transversal movement of the bench	0,5-12
Vertical handwheel precision	0,001
Vertical handwheel 1 turn	5
Precision transversal handwheel	0,02
Cross handwheel 1 turn	5
Power of headstock motor	5,5
Power of hydraulic motor	2,2
Power of cross feed motor	0,09
Power of cooling motor	0,09
Electrical voltage	220-380 V - 50/60 Hz
Grinding wheel [øExt. x width x ø In.]	355x40x127
Dimensions (length x width x height)	2750x2200x2250
Weight	2850/3050



Standard equipment

- Electromagnetic chuck
(magnetizer/demagnetizer)

- Coolant System

- Diamond Support

- Automatic Movements X - Y - Z

- FAGOR Digital Readout X Z

- Y axis ballscrew

- Overhead Parallel dresser

- Work light

- CE Certificate